BEVMAX 4

45 SELECT • MODEL 5800-4

THE BEST CONSUMER EXPERIENCE IN VENDING

PRODUCT DISPLAY • VARIETY • CONVENIENCE • RELIABILITY

**BEST IN CLASS
45 SELECTIONS
360 UNIT CAPACITY**

**MEETS ANSI
AND NEW ADA
REQUIREMENTS**

**EXCEEDS ENERGY
STAR TIER 3 AND
2013 D.O.E.
STANDARDS**

CRANE MERCHANDISING SYSTEMS

BEVMAX 4

45 SELECT • MODEL 5800-4

...two times more energy efficient than machines made five years ago -

ENERGY EFFICIENT REFRIGERATION PLATFORM

	kWh per year	Increased Operating Costs per Year	
BevMax4	1423		
Competitor A	2042	$68.27	+43%
Competitor B	2100	$74.67	+48%
5-Year Old Machine	2871	$159.71	+102%

Based on the national average cost per kWh in January 2009 of $0.1103/kWh. Actual energy usage may vary based on environmental conditions.

Tier 3

*BevMax4 exceeds ENERGY STAR Tier 3 Standards. The only Glass Front to exceed the Department of Energy 2013 Conservation Standards.*

ENERGY STAR

Only BevMax4 has been designed to enhance the consumer experience and meet the operational needs of bottlers and vending operators.

45 Selections + 360 Capacity add big value

RELIABILITY.

The most reliable, dependable vending solution proven by independent lab tests of 20,000 operating vends; 80,000 vend life-cycles and comprehensive field testing exceeding 238,000 vends.

VARIETY.

Reduce sold-out column potential. Add more facings of high turnover products. Create more variety to appeal to broad consumer segments and daypart consumption. Make more efficient, bigger case drops.

EFFICIENCY.

A "shimless" vend mechanism addresses costly labor and service concerns. Load any package in any position. Eliminate loading errors. Load fast with both hands. Bottles remain firmly in place *(even if the machine is rocked)*.

SPEED.

Who likes to wait in line? BevMax4 delivers product in only 8-seconds. Faster delivery time increases sales; speed of service and customer satisfaction.

SIMPLIFIED MAINTENANCE

Low profile modular refrigeration platform removes from the front or the back of the machine.

Front Removal

Back Removal

SPECIFICATIONS

DIMENSIONS
72" H x 47" W x 32" D
(183cm H x 120cm W x 82cm D)

WEIGHT
764 lbs. empty (347 kg)

ELECTRICAL
115 VAC, 60Hz, 10.2 amps
MDB Level 3 Controller

REFRIGERATION
134A CFC-Free Refrigerant Gas
1/3 HP Compressor

CERTIFICATIONS
UL, CUL, CE, FCC, NOM, CTICK